

Stain and Varnish – Gloss/ Satin

Page 1 of 2
Resource Code 1107 Line – Satin
1108 Line – Gloss
July 2003

DESCRIPTION

- Wattyl Stain and Varnish is a convenient “one step” stain and clear finish that protects and beautifies all interior timber surfaces.

PRINCIPAL CHARACTERISTICS

- Suitable for interior use only.
- Suitable for awkward areas where a stain may be difficult to apply.
- May overcoated with Wattyl ESTAPOL® Gloss/Satin/Matt (D5.19) for extra durability.

COLOURS AND GLOSS

- Refer to the appropriate Wattyl colour card
- Satin or Gloss

BASIC DATA

- **Surface Dry** Six (6) hours
- **Recoat** Twenty four (24) hours
All figures are quoted at 25 °C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 12 M²/L (depending on the texture and porosity of the surface.)
- **Wet Film Thickness** 83 microns
- **Dry Film Thickness** 37 microns
- **Thinning** The first coat may be thinned with up to 5-10% mineral turps for application to new timber. No thinning is required for subsequent coats.
- **Clean up** Thoroughly clean equipment with mineral turps.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Suitable for use on all interior woodwork, louvre doors, built-in furniture and panelling.
- **Not** suitable for MDF board unless previously sealed with Wattyl Water Based ESTAPOL® Clear – Gloss/Satin (D5.13).
- **Not** recommended for use over Wattyl ESTAPOL® 7008 (D5.07).
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- **New Timber**
Ensure all new timber is free of dirt or grease and dry. Fill nail holes or cracks with Wattyl Timber Putty (D1.08) in a matching colour. Allow to dry. Sand smooth and remove dust.
- **Previously Coated Surfaces**
For unknown surfaces, it is recommended that the surface be thoroughly stripped, sanded and cleaned before application. Surfaces previously coated with Wattyl Stain and Varnish or Wattyl ESTAPOL® Gloss/Satin/Matt (D5.19) in sound condition should be cleaned free from grease, wax or polish then sanded with fine sandpaper and dusted off. Treat bare areas as new timber.

INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Where more than one can is required, box all cans together in a clean metal or glass container and stir well before use.
- Apply one (1) or two (2) coats, to a correctly prepared surface using a quality brush. Lightly sand between coats.
- Before application test the colour on a timber off cut or a section of the job which is not visible. If the colour is too strong, thin up to 10% with mineral turps. To deepen the colour, apply additional coats of Wattyl Stain and Varnish. When the desired colour is achieved, apply one or two coats of Wattyl ESTAPOL® Gloss/Satin/Matt (D5.19), this will enhance durability without deepening the colour. **Do not** use Wattyl ESTAPOL® 7008 (D5.07).

SAFETY PRECAUTIONS

- **Caution** Flammable
Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 250, 500ml, 1 and 4 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.