

# PROFESSIONAL CHOICE EASY FLOW™ Satin Enamel

Page 1 of 2  
Resource Code 125804  
July 2003

## DESCRIPTION

- Wattyl PROFESSIONAL CHOICE EASY FLOW™ Satin Enamel is a high quality hard wearing interior satin enamel.

## PRINCIPAL CHARACTERISTICS

- Suitable for interior use only.
- Superior performance and durability.
- Excellent flow and coverage.

## COLOURS AND GLOSS

- White base only. May also be tinted to the Wattyl colour range or other competitor colour ranges through the Wattyl tinting system.
- Satin

## BASIC DATA

- **Surface Dry** Four (4) hours.
- **Recoat** Twenty Four (24) hours.
- **Fully Cured** Seven (7) days.  
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 14 M<sup>2</sup>/L (depending on the surface porosity and method of application)
- **Wet Film Thickness** 63 microns
- **Dry Film Thickness** 34 microns
- **Thinning** If required, thin sparingly with mineral turps
- **Clean up** Thoroughly clean equipment with mineral turps.

## RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- For use on suitably prepared interior timber, plaster, cement, fibre cement, paperfaced plasterboard, and previously painted surfaces.
- Ideal for interior ceilings and walls in kitchens, bathrooms, laundries, walls and ceilings, also interior doors, windows and fixtures where a high performance and durable finish is required.
- Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed prior to coating. Remove all traces of gloss by sanding. Fill holes and cracks with a suitable spackling compound.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- Freshly applied material must be protected from steam and condensation for a minimum of forty eight (48) hours.
- Any mould spots must be treated with bleach, and then rinsed with clean water before painting. For added protection use Wattyl Fungicidal Additive in the paint.
- For specific substrate preparation, see relevant specification sheets.

## INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply two coats to a correctly prepared surface by brush, roller or spray equipment.

## SAFETY DATA

- **Caution** Flammable  
Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spill material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.

**SAFETY DATA - Continued**

- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**  
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).  
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.  
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.  
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

**ADDITIONAL DATA**

- Available in 4, 10 and 20 litre containers.
- To avoid excessive yellowing, the APMF recommends that if a white or a pale colour enamel is being used, the following precautions to be take:
  1. Ensure maximum ventilation.
  2. Avoid applying water-based paint in the vicinity of the new enamel work.
  3. Avoid using household cleaners containing high levels of ammonia for a period of two weeks after application of the enamel.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- Approved to APAS 0015/3.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.