

PROFESSIONAL CHOICE™ FD Undercoat

Page 1 of 2
Resource Code 126102
July 2003

DESCRIPTION

- Watty Professional Choice™ FD Undercoat is a premium alkyd based, general purpose undercoat.

PRINCIPAL CHARACTERISTICS

- Suitable for interior or exterior use.
- Specifically designed to allow short recoat times and resistance to wrinkling.
- High opacity

COLOURS AND GLOSS

- White, may be tinted as required.

BASIC DATA

- **Surface Dry** Four (4) hours
- **Recoat** Six (6) hours minimum
- **Fully Cured** Seven (7) days
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 14 M²/L (depending on the texture, surface porosity and method of application).
- **Wet Film Thickness** 72 microns
- **Dry Film Thickness** 40 microns
- **Thinning** If necessary, thin sparingly with mineral turps.
- **Clean up** Thoroughly clean equipment with mineral turps.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- **Not** suitable for use on MDF board.
- Suitable for use as an undercoat on interior bare timber and hardboards. For exterior timber Watty Professional Choice™ FD Undercoat must be used **over** Watty Professional Choice™ Alkyd Timber Primer (D9.02).
- Ideal for use in alkyd based systems over suitably prepared concrete and brick surfaces.
- Ensure the surface is clean and dry. All cementitious surfaces must be fully cured. All loose, peeling and flaking material must be removed prior to coating. Fill holes and cracks with a suitable filling compound. Allow to dry, and sand to an even finish.
- For interior timber fill nail holes and cracks etc. with Watty Timber Putty (D1.08) **prior** to the application of Watty Professional Choice™ FD Undercoat.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- Any mould spots must be treated with bleach, and then rinsed with clean water before painting. For added protection use Watty Fungicidal Additive (D1.03) in the paint.

INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply one (1) or two (2) coats to a correctly prepared surface by brush, roller or spray equipment.

SAFETY DATA

- **Caution** Flammable
Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.

SAFETY DATA - Continued

- **First Aid**

If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).

If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.

If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.

If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 4, 10 and 20 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Watty Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Watty products. Watty recommends that:

(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive.

3. Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Watty Office.

4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.