

# Traditional Stain

Page 1 of 2  
Resource Code 1126-Line  
July 2003

## DESCRIPTION

- Wattyl Traditional Stain (CRAFTSMAN®, FRS) is dye type stain suitable for interior use on all non-absorbent timbers and veneers.

## PRINCIPAL CHARACTERISTICS

- Suitable for interior use only.
- Used by quality furniture craftsman for over 40 years.

## COLOURS AND GLOSS

- Colour – refer to the Wattyl Interior Timber Finishes Colour Card.

## BASIC DATA

- **Surface Dry** Thirty (30) minutes.
- **Recoat** Four (4) hours.
- **Fully Cured** Seven (7) days.  
All figures are quoted at 25 °C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 12 M<sup>2</sup>/L (depending on the texture, surface porosity and method of application).
- **Wet Film Thickness** N/A
- **Dry Film Thickness** N/A
- **Thinning** Thin as required with Wattyl Traditional Stain Reducer.
- **Clean up** Thoroughly clean equipment with Wattyl Traditional Stain Reducer.

## RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- **Not Suitable** for use on MDF board.
- **Do not** use on timber floors.
- Suitable for interior application such as built-in and free standing furniture, wall panelling, bookshelves, doors, cupboards.
- For absorbent timbers such as pine and particle board use Wattyl Interior Stain(D5.01).
- Ensure all new timber is free of dirt or grease and dry. Fill nail holes or cracks with Wattyl Timber Putty (D1.08) in a matching colour. Allow to dry. Sand smooth and remove dust.
- Test the colour first on a timber off cut or a section of the job that does not show. If the colour is too strong, dilute with Wattyl Traditional Stain Reducer.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

## INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply generously with a lint free clean cloth pad wiping along the grain to even out the stain. On large areas stain one section at a time so that the stain does not dry before the excess is removed. On application is usually sufficient, subsequent applications will darken the colour and mask the grain.

### INSTRUCTIONS FOR USE - continued

- **Note:** Wattyl Traditional Stain is not a finish. It must be overcoated with Wattyl ESTAPOL® Gloss, Satin, Matt (D5.19), Wattyl ESTAPOL® 7008 (D5.07) or Wattyl Water Based ESTAPOL® Clear Gloss/Satin (D5.13).
- **Note:** If a completely, smooth finish is desired, fill open grained timbers with Wattyl Grain Filler (D1.09). Apply the filler **before** staining or mix Traditional Stain into the Grain Filler. If mixing into the Grain Filler add 10% Traditional Stain instead of 25% mineral turps.
- When Traditional Stain has been mixed with Grain Filler, topcoat with Wattyl ESTAPOL® Gloss, Satin, Matt (D5.19). **Do not** use Wattyl ESTAPOL® 7008 (D5.07).

### SAFETY PRECAUTIONS

- **Caution** Flammable  
Provide adequate ventilation.  
Wear rubber gloves. Some gloves may not be resistant to Wattyl Traditional Stain.
- **Spills and Disposal** Do not allow spill material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**  
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).  
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.  
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.  
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

### ADDITIONAL DATA

- Available in 250, 500 ml, 1 and 4 litre containers.
- Where more than one can of stain is required to complete the job, combine all cans in a metal container and stir well before using.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.  
2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.  
3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.  
4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.