

# i.d™ Ultra Premium Matt

Page 1 of 2  
Resource Code 11730 - Line  
July 2003

## DESCRIPTION

- Wattyl i.d™ Ultra Premium Matt is a 100% acrylic wall paint, which produces a smooth, long lasting, elegant finish.

## PRINCIPAL CHARACTERISTICS

- Suitable for interior use only.
- Excellent covering power and adhesion.
- Applies with minimum roller splatter.
- Excellent scuff resistance and stain removal properties.

## COLOURS AND GLOSS

- Bases may be tinted as required. Refer to the appropriate i.d™ Inside Colour Card. May also be tinted to the Wattyl colour range or other competitor colour ranges through the Wattyl tinting system.
- Matt.

## BASIC DATA

- **Surface Dry** Thirty (30) minutes.
- **Recoat** Two (2) hours.
- **Fully Cured** Seven (7) days.  
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** 16 M<sup>2</sup>/L (depending on the surface porosity and method of application)
- **Wet Film Thickness** 63 microns
- **Dry Film Thickness** 26 microns
- **Thinning** If required, thin with up to 5% water.
- **Clean up** Thoroughly clean equipment with water.

## RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- For use on suitably prepared timber, brick, cement, paperfaced plasterboard and previously painted surfaces.
- Ideal for domestic kitchens, bathrooms, laundries, passageways and other high usage living areas.
- Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed prior to painting.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- Freshly applied material must be protected from steam and condensation for a minimum of forty eight (48) hours.
- Any mould spots must be treated with bleach, and then rinsed with clean water before painting. For added protection use Wattyl Fungicidal Additive (D1.03) in the paint.
- For specific substrate preparation, see relevant specification sheets.

## INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply two coats to a correctly prepared surface by brush, roller or spray equipment.
- Ensure brushes and rollers are or only slightly damp with water before use.

## SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.

### SAFETY DATA - continued

- **First Aid**

If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).

If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.

If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.

If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

### ADDITIONAL DATA

- Available in 1, 2, 4, 10 and 20 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- Leave seven days after application of final coat before washing.
- When subject to steam or condensation, water based paints may develop a stain, which can be removed with a damp cloth.
- Avoid exposure to excessive steam or condensation for 48 hours after application of the final coat.
- Approved to APAS 0260/4
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.